



AULA AU3.L1.600.XY

Typ: Wandleuchte

Lampenschirm: Acrylglas

Leuchte: lackiertes Stahlblech RAL 9016 (.41), RAL 7012 (.47), RAL Argento dorato (.70), RAL Copper (.72), RAL Bronze (.73), RAL Brass (.74)



W	K	Module luminous flux lm	Luminaire luminous flux lm	A	B	C	DALI 2	IK06	IP20	Bluetooth	Track System	Weight
20,9	3000	2698	2535	640	120	95	M	-	-	Q*	-	1800

Lucis AU3.L1.600.X AULA LED / LDC (Polar)

Spannung: 230V

IK Code: IK06

Vorschalgerät: Driver

CRI: >90

LED-Lebensdauer: L80/F10 50000 Stunden

Watt: 20,9 W

Farbtemperatur: 3000 K

Module luminous flux: 2698 lm

Luminaire luminous flux: 2535 lm

A: 640 mm

B: 120 mm

C: 95 mm

Dali 2: Verfügbar

Bewegungsmelder: Nicht Verfügbar

Notlichtmodul: Nicht Verfügbar

Bluetooth-Steuerung: Verfügbar auf Anfrage

Track-System: Nicht Verfügbar

Sádrokarton: Nicht Verfügbar

Gewicht: 1800 g

Luminaire: Lucis AU3.L1.600.X AULA LED
Lamps: 1 x LED G6

