

AULA AU1.L1.600.XY

**Type:** luminaire de plafond et mural

**Abat-jour:** verre acrylique

**Luminaire:** tôle d'acier revêtue RAL 9016 (.41), RAL 7012 (.47), RAL Argento dorato (.70), RAL Copper (.72), RAL Bronze (.73), RAL Brass (.74)



W	K	Module lumineux flux lm	Luminaire lumineux flux lm	A	B	C	DALI 2	Emergency	Bluetooth	Track system	Weight
20,9	3000	2698	2535	640	125	50	M	-	-	-	1700

Lucis AU1.L1.600.X AULA LED / LDC (Polar)

**Tension:** 230V

**IK code:** IK06

**Ballaste:** Driver

**CRI:** >90

**La vie de LED:** L80/F10 50000 heures

**Watt:** 20,9 W

**Température Couleur:** 3000 K

**Module lumineux flux:** 2698 lm

**Luminaire lumineux flux:** 2535 lm

**A:** 640 mm

**B:** 125 mm

**C:** 50 mm

**Dali 2:** Disponible

**Capteur de mouvement:** Non disponible

**Module d'urgence:** Non disponible

**Contrôle Bluetooth:** Non disponible

**Track system:** Non disponible

**Sádrokarton:** Non disponible

**Poids:** 1700 g

Luminaire: Lucis AU1.L1.600.X AULA LED  
Lamps: 1 x LED G6

