

AULA AU1.L2.900.XY

Type: luminaire de plafond et mural

Abat-jour: verre acrylique

Luminaire: tôle d'acier revêtue RAL 9016 (.41), RAL 7012 (.47), RAL Argento dorato (.70), RAL Copper (.72), RAL Bronze (.73), RAL Brass (.74)



W	K	Module lumineux flux lm	Luminaire lumineux flux lm	A	B	C	DALI 2	🚶	🚶	📶	📄	📦	
30,7	4000	4209	3955	920	125	50	M	-	-	-	-	-	2300

Lucis AU1.L2.900.X AULA LED / LDC (Polar)

Tension: 230V

IK code: IK06

Ballaste: Driver

CRI: >90

La vie de LED: L80/F10 50000 heures

Watt: 30,7 W

Température Couleur: 4000 K

Module lumineux flux: 4209 lm

Luminaire lumineux flux: 3955 lm

A: 920 mm

B: 125 mm

C: 50 mm

Dali 2: Disponible

Capteur de mouvement: Non disponible

Module d'urgence: Non disponible

Contrôle Bluetooth: Non disponible

Track system: Non disponible

Sádrokarton: Non disponible

Poids: 2300 g

Luminaire: Lucis AU1.L2.900.X AULA LED
Lamps: 1 x LED G6

