

AULA AU1.L1.1500.XY

**Type:** ceiling and wall lamp

**Lampshade:** acrylic glass

**Light body:** painted steel plate RAL 9016 (.41), RAL 7012 (.47), RAL Argento dorato (.70), RAL Copper (.72), RAL Bronze (.73), RAL Brass (.74)



W	K	Module luminous flux lm	Luminaire luminous flux lm	A	B	C	DALI 2	Motion sensor	Emergency module	Bluetooth	Track system	Weight
51	3000	6745	6338	1500	125	50	M	-	-	-	-	3700

Lucis AU1.L1.1500.X AULA LED / LDC (Polar)

**Voltage:** 230V

**IK code:** IK06

**Ballast:** Driver

**CRI:** >90

**LED life:** L80/F10 50000 hours

**Watt:** 51 W

**Color temperature:** 3000 K

**Module luminous flux:** 6745 lm

**Luminaire luminous flux:** 6338 lm

**A:** 1500 mm

**B:** 125 mm

**C:** 50 mm

**Dali 2:** Available

**Motion sensor:** Not available

**Emergency module:** Not available

**Bluetooth control:** Not available

**Track system:** Not available

**Sádrokarton:** Not available

**Weight:** 3700 g

Luminaire: Lucis AU1.L1.1500.X AULA LED  
Lamps: 1 x LED G6

