


ASTERION S5.L2.A350.0W

Type: wall lamp

Lampshade: white, hand-blown, three-layered glass, satin opal matt

Light body: white painted steel plate



| W | K | Module luminous flux lm | Luminaire luminous flux lm | A | B | C | DALI 2 | Motion sensor | Emergency module | Bluetooth control | Track system | Weight |
|-----|------|-------------------------|----------------------------|-----|-----|-----|--------|---------------|------------------|-------------------|--------------|--------|
| 4,8 | 4000 | 601 | 453 | 350 | 165 | 175 | M | - | - | - | - | 1500 |

Lucis S5.L2.A350.0W ASTERION LED / LDC (Polar)

Voltage: 230V

IK code: IK01

Ballast: Driver

CRI: >90

LED life: L80/F10 50000 hours

Watt: 4,8 W

Color temperature: 4000 K

Module luminous flux: 601 lm

Luminaire luminous flux: 453 lm

A: 350 mm

B: 165 mm

C: 175 mm

Dali 2: Available

Motion sensor: Not available

Emergency module: Not available

Bluetooth control: Not available

Track system: Not available

Sádrokarton: Not available

Weight: 1500 g

Luminaire: Lucis S5.L2.A350.0W ASTERION LED
Lamps: 1 x LED G6

