



ELIOS ZK.K2.E120.XY

Type: suspension lamp

Lampshade: acrylic glass for LED

Metal parts: painted aluminium – RAL 9016 (.41), RAL 3004 (.42), RAL 7023 (.43), RAL 5000 (.44) or RAL 9005 (.45)

Pendant: transparent cable



W	K	Module luminous flux lm	Luminaire luminous flux lm	A	B	C	DALI 2	Motion sensor	Emergency module	Bluetooth	Track system	Weight
9,6	4000	1295	1047	120	135	1500	M	-	P*	Q*	R*	D* 1100

Voltage: 230V

IK code: IK06

Ballast: Driver

CRI: >90

LED life: L80/F10 50000 hours

Watt: 9,6 W

Color temperature: 4000 K

Module luminous flux: 1295 lm

Luminaire luminous flux: 1047 lm

A: 120 mm

B: 135 mm

C: 1500 mm

Dali 2: Available

Motion sensor: Not available

Emergency module: Available on inquiry

Bluetooth control: Available on inquiry

Track system: Available on inquiry

Sádrokarton: Available on inquiry

Weight: 1100 g

Lucis ZK.K2.E120.X ELIOS LED / LDC (Polar)

Luminaire: Lucis ZK.K2.E120.X ELIOS LED
Lamps: 1 x LED G5

