

ELIOS ZK3.K1.E220.XY

Type: suspension lamp

Lampshade: acrylic glass

Metal parts: painted aluminium – RAL 9016 (.41), RAL 3004 (.42), RAL 7023 (.43), RAL 5000 (.44) or RAL 9005 (.45)

Pendant: steel wire suspension with a transparent cable



W	K	Module luminous flux lm	Luminaire luminous flux lm	A	B	C	DALI 2	IK06	Emergency	Bluetooth	Track system	Weight
18,2	3000	2378	1922	220	85	1500	M	-	P*	Q*	-	1700

Voltage: 230V

IK code: IK06

Ballast: Driver

CRI: >90

LED life: L80/F10 50000 hours

Watt: 18,2 W

Color temperature: 3000 K

Module luminous flux: 2378 lm

Luminaire luminous flux: 1922 lm

A: 220 mm

B: 85 mm

C: 1500 mm

Dali 2: Available

Motion sensor: Not available

Emergency module: Available on inquiry

Bluetooth control: Available on inquiry

Track system: Not available

Sádrokarton: Not available

Weight: 1700 g

Lucis ZK3.K1.E220.X ELIOS LED / LDC (Polar)

Luminaire: Lucis ZK3.K1.E220.X ELIOS LED
Lamps: 1 x LED G5

