


ELIOS S7.K1.E120.XY

**Type:** luminaire plafonnier

**Abat-jour:** verre acrylique

**Luminaire:** aluminium laqué - RAL 9016 (.41), RAL 3004 (.42), RAL 7023 (.43), RAL 5000 (.44) ou RAL 9005 (.45)



W	K	Module luminous flux lm	Luminaire luminous flux lm	A	B	DALI 2	Emergency	Bluetooth	Track system	Weight
9,6	3000	1237	1001	120	63	M	-	-	-	500

**Tension:** 230V

**IK code:** IK06

**Ballaste:** Driver

**CRI:** >90

**La vie de LED:** L80/F10 50000 heures

**Watt:** 9,6 W

**Température Couleur:** 3000 K

**Module luminous flux:** 1237 lm

**Luminaire luminous flux:** 1001 lm

**A:** 120 mm

**B:** 63 mm

**Dali 2:** Disponible

**Capteur de mouvement:** Non disponible

**Module d'urgence:** Non disponible

**Contrôle Bluetooth:** Non disponible

**Track system:** Non disponible

**Sádrokarton:** Non disponible

**Poids:** 500 g

Lucis S7.K1.E120.X ELIOS LED / LDC (Polar)

Luminaire: Lucis S7.K1.E120.X ELIOS LED  
Lamps: 1 x LED G5

