


ELIOS S7.K3.E120.XY

Typ: Deckenleuchte

Lampenschirm: Acrylglas

Leuchte: Aluminium lackiert – RAL 9016 (.41), RAL 3004 (.42), RAL 7023 (.43), RAL 5000 (.44) oder RAL 9005 (.45)



W	K	Module luminous flux lm	Luminaire luminous flux lm	A	B	DALI 2	IK06	IK08	Bluetooth	Track-System	Sádrokarton	Gewicht
6,7	3000	899	727	120	63	M	-	-	-	-	-	500

Spannung: 230V

IK Code: IK06

Vorschalgerät: Driver

CRI: >90

LED-Lebensdauer: L80/F10 50000 Stunden

Watt: 6,7 W

Farbtemperatur: 3000 K

Module luminous flux: 899 lm

Luminaire luminous flux: 727 lm

A: 120 mm

B: 63 mm

Dali 2: Verfügbar

Bewegungsmelder: Nicht Verfügbar

Notlichtmodul: Nicht Verfügbar

Bluetooth-Steuerung: Nicht Verfügbar

Track-System: Nicht Verfügbar

Sádrokarton: Nicht Verfügbar

Gewicht: 500 g

Lucis S7.K3.E120.X ELIOS LED / LDC (Polar)

Luminaire: Lucis S7.K3.E120.X ELIOS LED
Lamps: 1 x LED G5

