


ELIOS S7.K3.E120.XY

**Type:** ceiling lamp

**Lampshade:** acrylic glass

**Light body:** painted aluminium – RAL 9016 (.41), RAL 3004 (.42), RAL 7023 (.43), RAL 5000 (.44) or RAL 9005 (.45)



W	K	Module luminous flux lm	Luminaire luminous flux lm	A	B	DALI 2	☺	☺	☺	☺	☺	☺
6,7	3000	899	727	120	63	M	-	-	-	-	-	500

**Voltage:** 230V

**IK code:** IK06

**Ballast:** Driver

**CRI:** >90

**LED life:** L80/F10 50000 hours

**Watt:** 6,7 W

**Color temperature:** 3000 K

**Module luminous flux:** 899 lm

**Luminaire luminous flux:** 727 lm

**A:** 120 mm

**B:** 63 mm

**Dali 2:** Available

**Motion sensor:** Not available

**Emergency module:** Not available

**Bluetooth control:** Not available

**Track system:** Not available

**Sádrokarton:** Not available

**Weight:** 500 g

Lucis S7.K3.E120.X ELIOS LED / LDC (Polar)

Luminaire: Lucis S7.K3.E120.X ELIOS LED  
Lamps: 1 x LED G5

