


ELIOS S7.K3.E220.XY

Type: luminaire plafonnier

Abat-jour: verre acrylique

Luminaire: aluminium laqué - RAL 9016 (.41), RAL 3004 (.42), RAL 7023 (.43), RAL 5000 (.44) ou RAL 9005 (.45)



W	K	Module luminous flux lm	Luminaire luminous flux lm	A	B	DALI 2	IK 10	IK 08	Bluetooth	Track system	Weight	
12,5	3000	1691	1366	220	63	M	-	-	Q*	-	-	1100

Tension: 230V

IK code: IK06

Ballaste: Driver

CRI: >90

La vie de LED: L80/F10 50000 heures

Watt: 12,5 W

Température Couleur: 3000 K

Module luminous flux: 1691 lm

Luminaire luminous flux: 1366 lm

A: 220 mm

B: 63 mm

Dali 2: Disponible

Capteur de mouvement: Non disponible

Module d'urgence: Non disponible

Contrôle Bluetooth: Disponible sur demande

Track system: Non disponible

Sádrokarton: Non disponible

Poids: 1100 g

Lucis S7.K3.E220.X ELIOS LED / LDC (Polar)

Luminaire: Lucis S7.K3.E220.X ELIOS LED
Lamps: 1 x LED G5

