


## ELIOS S7.K4.E220.XY

**Typ:** Deckenleuchte

**Lampenschirm:** Acrylglas

**Leuchte:** Aluminium lackiert – RAL 9016 (.41), RAL 3004 (.42), RAL 7023 (.43), RAL 5000 (.44) oder RAL 9005 (.45)



| W    | K    | Module luminous flux lm | Luminaire luminous flux lm | A   | B  | DALI 2 | IK06 | IK08 | Bluetooth | Track-System | Sádrokarton | Weight |
|------|------|-------------------------|----------------------------|-----|----|--------|------|------|-----------|--------------|-------------|--------|
| 12,5 | 4000 | 1771                    | 1431                       | 220 | 63 | M      | -    | -    | Q*        | -            | -           | 1100   |

**Spannung:** 230V

**IK Code:** IK06

**Vorschalgerät:** Driver

**CRI:** >90

**LED-Lebensdauer:** L80/F10 50000 Stunden

**Watt:** 12,5 W

**Farbtemperatur:** 4000 K

**Module luminous flux:** 1771 lm

**Luminaire luminous flux:** 1431 lm

**A:** 220 mm

**B:** 63 mm

**Dali 2:** Verfügbar

**Bewegungsmelder:** Nicht Verfügbar

**Notlichtmodul:** Nicht Verfügbar

**Bluetooth-Steuerung:** Verfügbar auf Anfrage

**Track-System:** Nicht Verfügbar

**Sádrokarton:** Nicht Verfügbar

**Gewicht:** 1100 g

Lucis S7.K4.E220.X ELIOS LED / LDC (Polar)

Luminaire: Lucis S7.K4.E220.X ELIOS LED  
Lamps: 1 x LED G5

