


ELIOS S7.K4.E220.XY

**Type:** ceiling lamp

**Lampshade:** acrylic glass

**Light body:** painted aluminium – RAL 9016 (.41), RAL 3004 (.42), RAL 7023 (.43), RAL 5000 (.44) or RAL 9005 (.45)



W	K	Module luminous flux lm	Luminaire luminous flux lm	A	B	DALI 2	☺	☺	☺	☺	☺	☺
12,5	4000	1771	1431	220	63	M	-	-	Q*	-	-	1100

**Voltage:** 230V

**IK code:** IK06

**Ballast:** Driver

**CRI:** >90

**LED life:** L80/F10 50000 hours

**Watt:** 12,5 W

**Color temperature:** 4000 K

**Module luminous flux:** 1771 lm

**Luminaire luminous flux:** 1431 lm

**A:** 220 mm

**B:** 63 mm

**Dali 2:** Available

**Motion sensor:** Not available

**Emergency module:** Not available

**Bluetooth control:** Available on inquiry

**Track system:** Not available

**Sádrokarton:** Not available

**Weight:** 1100 g

Lucis S7.K4.E220.X ELIOS LED / LDC (Polar)

Luminaire: Lucis S7.K4.E220.X ELIOS LED  
Lamps: 1 x LED G5

