


JUNO LED ZK.K3.J1.XY

Type: suspension lamp

Lampshade: acrylic glass

Metal parts: painted aluminium in diverse colours, (combination) RAL 9003 (.31), RAL 3022 (.32), RAL 7021 (.33), RAL 6034 (.34), RAL 1018 (.35), RAL 7023 (.37), RAL 5009 (.38)

Pendant: self-supporting white X-01 or black X-02 to X-23 cable reinforced with a steel wire



W	K	Module luminous flux lm	Luminaire luminous flux lm	A	B	C	DALI 2	Motion sensor	Emergency module	Bluetooth	Track system	Weight	
6,7	3000	899	712	150	150	2000	M	-	P*	-	R*	D*	1300

Voltage: 230V

IK code: IK06

Ballast: Driver

CRI: >90

LED life: L80/F10 50000 hours

Watt: 6,7 W

Color temperature: 3000 K

Module luminous flux: 899 lm

Luminaire luminous flux: 712 lm

A: 150 mm

B: 150 mm

C: 2000 mm

Dali 2: Available

Motion sensor: Not available

Emergency module: Available on inquiry

Bluetooth control: Not available

Track system: Available on inquiry

Sádrokarton: Available on inquiry

Weight: 1300 g

Lucis ZK.K3.J1.X JUNO LED / LDC (Polar)

Luminaire: Lucis ZK.K3.J1.X JUNO LED
Lamps: 1 x LED G5

