


MAIA PMMA S1.L2W.Y PA

**Type:** luminaire mural

**Abat-jour:** en verre acrylique PMMA opale

**Luminaire:** tôle en acier peint en blanc



W	K	Module luminous flux lm	Luminaire luminous flux lm	A	B	C	DALI 2	🚶	🚪	📶	📄	🏷️
13,5	4000	1682	1509	150	300	75	M	O*	-	-	-	1200

Lucis S1.L2W PA MAIA LED / LDC (Polar)

**Tension:** 230V

**IK code:** IK06

**Ballaste:** Driver

**CRI:** >90

**La vie de LED:** L80/F10 50000 heures

**Watt:** 13,5 W

**Température Couleur:** 4000 K

**Module luminous flux:** 1682 lm

**Luminaire luminous flux:** 1509 lm

**A:** 150 mm

**B:** 300 mm

**C:** 75 mm

**Dali 2:** Disponible

**Capteur de mouvement:** Disponible sur demande

**Module d'urgence:** Non disponible

**Contrôle Bluetooth:** Non disponible

**Track system:** Non disponible

**Sádrokarton:** Non disponible

**Poids:** 1200 g

Luminaire: Lucis S1.L2W PA MAIA LED  
Lamps: 1 x LED G6

