

MAIA A ZKS.L2A.M500.Y

**Type:** suspension lamp

**Lampshade:** white, hand-blown, three-layered glass, satin opal matt

**Metal parts:** white painted steel plate

**Pendant:** white cable

Driver of the luminaire is placed inside the ceiling rose (LED version).



W	K	Module luminous flux lm	Luminaire luminous flux lm	A	B	C	DALI 2	Motion sensor	Emergency module	Bluetooth	Track system	Weight
41,4	4000	6389	5265	150	500	2000	M	-	P*	Q*	-	D* 5000

Lucis ZKS.L2A.M500 MAIA LED / LDC (Polar)

**Voltage:** 230V

**IK code:** IK01

**Ballast:** Driver

**CRI:** >90

**LED life:** L80/F10 50000 hours

**Watt:** 41,4 W

**Color temperature:** 4000 K

**Module luminous flux:** 6389 lm

**Luminaire luminous flux:** 5265 lm

**A:** 150 mm

**B:** 500 mm

**C:** 2000 mm

**Dali 2:** Available

**Motion sensor:** Not available

**Emergency module:** Available on inquiry

**Bluetooth control:** Available on inquiry

**Track system:** Not available

**Sádrokarton:** Available on inquiry

**Weight:** 5000 g

Luminaire: Lucis ZKS.L2A.M500 MAIA LED  
Lamps: 1 x LED G6

