

MAIA A ZKS.L4A.M500.Y

Type: suspension lamp

Lampshade: white, hand-blown, three-layered glass, satin opal matt

Metal parts: white painted steel plate

Pendant: white cable

Driver of the luminaire is placed inside the ceiling rose (LED version).



W	K	Module luminous flux lm	Luminaire luminous flux lm	A	B	C	DALI 2	Motion sensor	Emergency module	Bluetooth	Track system	Weight	
31,3	4000	5022	4139	150	500	2000	M	-	P*	Q*	R*	D*	4600

Lucis ZKS.L4A.M500 MAIA LED / LDC (Polar)

Voltage: 230V

IK code: IK01

Ballast: Driver

CRI: >90

LED life: L80/F10 50000 hours

Watt: 31,3 W

Color temperature: 4000 K

Module luminous flux: 5022 lm

Luminaire luminous flux: 4139 lm

A: 150 mm

B: 500 mm

C: 2000 mm

Dali 2: Available

Motion sensor: Not available

Emergency module: Available on inquiry

Bluetooth control: Available on inquiry

Track system: Available on inquiry

Sádrokarton: Available on inquiry

Weight: 4600 g

Luminaire: Lucis ZKS.L4A.M500 MAIA LED
Lamps: 1 x LED G6

