

MAIA A ZKS.L1A.M580.Y

Type: suspension lamp

Lampshade: white, hand-blown, three-layered glass, satin opal matt

Metal parts: white painted steel plate

Pendant: white cable

Driver of the luminaire is placed inside the ceiling rose (LED version).



W	K	Module luminous flux lm	Luminaire luminous flux lm	A	B	C	DALI 2	Motion sensor	Emergency module	Bluetooth	Track system	Weight
16,1	3000	2033	1745	80	500	1500	M	-	P*	Q*	R*	D* 3200

Lucis ZKS.L1A.M580 MAIA LED / LDC (Polar)

Voltage: 230V

IK code: IK01

Ballast: Driver

CRI: >90

LED life: L80/F10 50000 hours

Watt: 16,1 W

Color temperature: 3000 K

Module luminous flux: 2033 lm

Luminaire luminous flux: 1745 lm

A: 80 mm

B: 500 mm

C: 1500 mm

Dali 2: Available

Motion sensor: Not available

Emergency module: Available on inquiry

Bluetooth control: Available on inquiry

Track system: Available on inquiry

Sádrokarton: Available on inquiry

Weight: 3200 g

Luminaire: Lucis ZKS.L1A.M580 MAIA LED
Lamps: 1 x LED G6

