

MAIA A PMMA ZKS.L1A.M320.Y PA


**Type:** suspension lamp; ceiling lamp

**Lampshade:** acrylic glass PMMA

**Metal parts:** white painted steel plate

**Pendant:** self-supporting white cable reinforced with a steel wire

Driver of the luminaire is placed inside the ceiling rose (LED version).



W	K	Module luminous flux lm	Luminaire luminous flux lm	A	B	C	DALI 2	Motion sensor	Emergency	Bluetooth	Track system	Weight	
22,9	3000	3289	3152	150	320	2000	M	-	P*	Q*	R*	D*	3000

Lucis ZKS.L1A.M320 PA MAIA LED / LDC (Polar)

**Voltage:** 230V

**IK code:** IK06

**Ballast:** Driver

**CRI:** >90

**LED life:** L80/F10 50000 hours

**Watt:** 22,9 W

**Color temperature:** 3000 K

**Module luminous flux:** 3289 lm

**Luminaire luminous flux:** 3152 lm

**A:** 150 mm

**B:** 320 mm

**C:** 2000 mm

**Dali 2:** Available

**Motion sensor:** Not available

**Emergency module:** Available on inquiry

**Bluetooth control:** Available on inquiry

**Track system:** Available on inquiry

**Sádrokarton:** Available on inquiry

**Weight:** 3000 g

Luminaire: Lucis ZKS.L1A.M320 PA MAIA LED  
Lamps: 1 x LED G6

