

MAIA A PMMA ZKS.L1A.M500.Y PA

**Type:** suspension lamp; ceiling lamp

**Lampshade:** acrylic glass PMMA

**Metal parts:** white painted steel plate

**Pendant:** self-supporting white cable reinforced with a steel wire

Driver of the luminaire is placed inside the ceiling rose (LED version).



W	K	Module luminous flux lm	Luminaire luminous flux lm	A	B	C	DALI 2	Motion sensor	Emergency module	Bluetooth	Track system	Weight
41,4	3000	6049	5743	150	500	2000	M	-	P*	Q*	-	D* 3800

Lucis ZKS.L1A.M500 PA MAIA LED / LDC (Polar)

**Voltage:** 230V

**IK code:** IK06

**Ballast:** Driver

**CRI:** >90

**LED life:** L80/F10 50000 hours

**Watt:** 41,4 W

**Color temperature:** 3000 K

**Module luminous flux:** 6049 lm

**Luminaire luminous flux:** 5743 lm

**A:** 150 mm

**B:** 500 mm

**C:** 2000 mm

**Dali 2:** Available

**Motion sensor:** Not available

**Emergency module:** Available on inquiry

**Bluetooth control:** Available on inquiry

**Track system:** Not available

**Sádrokarton:** Available on inquiry

**Weight:** 3800 g

Luminaire: Lucis ZKS.L1A.M500 PA MAIA LED  
Lamps: 1 x LED G6

