

MAIA A PMMA ZKS.L2A.M500.Y PA



Type: suspension lamp

Lampshade: acrylic glass PMMA

Metal parts: white painted steel plate

Pendant: self-supporting white cable reinforced with a steel wire

Driver of the luminaire is placed inside the ceiling rose (LED version).



W	K	Module luminous flux lm	Luminaire luminous flux lm	A	B	C	DALI 2	Motion sensor	Emergency module	Bluetooth	Track system	Weight
41,4	4000	6389	6065	150	500	2000	M	-	P*	Q*	-	D* 3800

Lucis ZKS.L2A.M500 PA MAIA LED / LDC (Polar)

Voltage: 230V

IK code: IK06

Ballast: Driver

CRI: >90

LED life: L80/F10 50000 hours

Watt: 41,4 W

Color temperature: 4000 K

Module luminous flux: 6389 lm

Luminaire luminous flux: 6065 lm

A: 150 mm

B: 500 mm

C: 2000 mm

Dali 2: Available

Motion sensor: Not available

Emergency module: Available on inquiry

Bluetooth control: Available on inquiry

Track system: Not available

Sádrokarton: Available on inquiry

Weight: 3800 g

Luminaire: Lucis ZKS.L2A.M500 PA MAIA LED
Lamps: 1 x LED G6

