

MAIA A PMMA ZKS.L3A.M500.Y PA

Type: suspension lamp; ceiling lamp

Lampshade: acrylic glass PMMA

Metal parts: white painted steel plate

Pendant: self-supporting white cable reinforced with a steel wire

Driver of the luminaire is placed inside the ceiling rose (LED version).



W	K	Module luminous flux lm	Luminaire luminous flux lm	A	B	C	DALI 2	Motion sensor	Emergency module	Bluetooth	Track system	Weight	
31,3	3000	4754	4513	150	500	2000	M	-	P*	Q*	R*	D*	3400

Lucis ZKS.L3A.M500 PA MAIA LED / LDC (Polar)

Voltage: 230V

IK code: IK06

Ballast: Driver

CRI: >90

LED life: L80/F10 50000 hours

Watt: 31,3 W

Color temperature: 3000 K

Module luminous flux: 4754 lm

Luminaire luminous flux: 4513 lm

A: 150 mm

B: 500 mm

C: 2000 mm

Dali 2: Available

Motion sensor: Not available

Emergency module: Available on inquiry

Bluetooth control: Available on inquiry

Track system: Available on inquiry

Sádrokarton: Available on inquiry

Weight: 3400 g

Luminaire: Lucis ZKS.L3A.M500 PA MAIA LED
Lamps: 1 x LED G6

