

MAIA A PMMA ZKS.L1A.M620.Y PA


Type: suspension lamp; ceiling lamp

Lampshade: acrylic glass PMMA

Metal parts: white painted steel plate

Pendant: self-supporting white cable reinforced with a steel wire

Driver of the luminaire is placed inside the ceiling rose (LED version).



| W | K | Module luminous flux lm | Luminaire luminous flux lm | A | B | C | DALI 2 | Motion sensor | Emergency module | Bluetooth | Track system | Weight |
|------|------|-------------------------|----------------------------|-----|-----|------|--------|---------------|------------------|-----------|--------------|---------|
| 74,3 | 3000 | 9545 | 8672 | 200 | 620 | 2000 | M | - | P* | Q* | - | D* 4400 |

Lucis ZKS.L1A.M620 PA MAIA LED / LDC (Polar)

Voltage: 230V

IK code: IK06

Ballast: Driver

CRI: >90

LED life: L80/F10 50000 hours

Watt: 74,3 W

Color temperature: 3000 K

Module luminous flux: 9545 lm

Luminaire luminous flux: 8672 lm

A: 200 mm

B: 620 mm

C: 2000 mm

Dali 2: Available

Motion sensor: Not available

Emergency module: Available on inquiry

Bluetooth control: Available on inquiry

Track system: Not available

Sádrokarton: Available on inquiry

Weight: 4400 g

Luminaire: Lucis ZKS.L1A.M620 PA MAIA LED
Lamps: 1 x LED G6

