

AULA AU1.L3.1200.XY

Type: luminaire de plafond et mural

Abat-jour: verre acrylique

Luminaire: tôle dacier revêtue RAL 9016 (.41), RAL 7012 (.47), RAL Argento dorato (.70), RAL Copper (.72), RAL Bronze (.73), RAL Brass (.74)



W	K	Module lumineux flux lm	Luminaire lumineux flux lm	A	B	C	DALI 2	IK06	IK08	Bluetooth	Emergency	Weight
20,2	3000	2800	2631	1200	125	50	M	-	-	-	-	3000

Lucis AU1.L3.1200.X AULA LED / LDC (Polar)

Tension: 230V

IK code: IK06

Ballaste: Driver

CRI: >90

La vie de LED: L80/F10 50000 heures

Watt: 20,2 W

Température Couleur: 3000 K

Module lumineux flux: 2800 lm

Luminaire lumineux flux: 2631 lm

A: 1200 mm

B: 125 mm

C: 50 mm

Dali 2: Disponible

Capteur de mouvement: Non disponible

Module d'urgence: Non disponible

Contrôle Bluetooth: Non disponible

Track system: Non disponible

Sádrokarton: Non disponible

Poids: 3000 g

Luminaire: Lucis AU1.L3.1200.X AULA LED
Lamps: 1 x LED G6

