

IZAR I I1.L3.600.XY

**Type:** wall lamp

**Lampshade:** acrylic glass in combination with acrylic glass white (.92), black (.93) or stainless steel (.83)

**Light body:** white painted steel plate



W	K	Module luminous flux lm	Luminaire luminous flux lm	A	B	C	DALI 2	Motion sensor	Emergency module	Bluetooth control	Track system	Weight
9,1	3000	1230	1017	600	80	40	M	-	-	Q*	-	1400

**Voltage:** 230V

**IK code:** IK06

**Ballast:** Driver

**CRI:** >90

**LED life:** L80/F10 50000 hours

**Watt:** 9,1 W

**Color temperature:** 3000 K

**Module luminous flux:** 1230 lm

**Luminaire luminous flux:** 1017 lm

**A:** 600 mm

**B:** 80 mm

**C:** 40 mm

**Dali 2:** Available

**Motion sensor:** Not available

**Emergency module:** Not available

**Bluetooth control:** Available on inquiry

**Track system:** Not available

**Sádrokarton:** Not available

**Weight:** 1400 g

Lucis I1.L3.600.X IZAR I LED / LDC (Polar)

Luminaire: Lucis I1.L3.600.X IZAR I LED  
Lamps: 1 x LED G6

