


ZERO S24.K1.Z280.Y

**Type:** ceiling and wall lamp

**Lampshade:** white, hand-blown, three-layered glass, satin opal matt

**Light body:** white painted steel plate



W	K	Module luminous flux lm	Luminaire luminous flux lm	A	B	C	D	DALI 2	Motion sensor	Emergency module	Bluetooth	Track system	Weight
12,5	3000	1691	1318	280	240	70	20	M	-	-	Q*	-	2100

**Voltage:** 230V

**IK code:** IK01

**Ballast:** Driver

**CRI:** >90

**LED life:** L80/F10 50000 hours

**Watt:** 12,5 W

**Color temperature:** 3000 K

**Module luminous flux:** 1691 lm

**Luminaire luminous flux:** 1318 lm

**A:** 280 mm

**B:** 240 mm

**C:** 70 mm

**D:** 20 mm

**Dali 2:** Available

**Motion sensor:** Not available

**Emergency module:** Not available

**Bluetooth control:** Available on inquiry

**Track system:** Not available

**Sádrokarton:** Not available

**Weight:** 2100 g

Lucis S24.K1.Z280 ZERO LED / LDC (Polar)

Luminaire: Lucis S24.K1.Z280 ZERO LED  
Lamps: 1 x LED G5

