

**POLARIS ZKS ZKS.L1.200.XY**



**Type:** suspension lamp

**Lampshade:** white, hand-blown, three-layered glass, satin opal matt

**Metal parts:** painted steel plate RAL 9003 (.31), RAL 9005 (.61), RAL chrom (.77), chrome (.80) or brass (.84)

**Pendant:** white or black self-carrying conductor reinforced with a steel wire

Driver of the luminaire is placed inside the ceiling rose.




W	K	Module luminous flux lm	Luminaire luminous flux lm	A	C	DALI 2	IK10	IK15	Bluetooth	Emergency	Weight
6,2	3000	804	714	200	2000	M	-	P*	Q*	R*	D* IJ* DIALux

Operator  
Telephone  
Fax  
e-Mail

**Lucis ZKS.L1.200.X POLARIS ZKS LED / LDC (Polar)**

Luminaire: Lucis ZKS.L1.200.X POLARIS ZKS LED  
Lamps: 1 x LED G6



**Voltage:** 230V

**IK code:** IK01

**Ballast:** Driver

**CRI:** >90

**LED life:** L80/F10 50000 hours

**Watt:** 6,2 W

**Color temperature:** 3000 K

**Module luminous flux:** 804 lm

**Luminaire luminous flux:** 714 lm

**A:** 200 mm

**C:** 2000 mm

**Dali 2:** Available

**Motion sensor:** Not available

**Emergency module:** Available on inquiry

**Bluetooth control:** Available on inquiry

**Track system:** Available on inquiry

**Sádrokarton:** Available on inquiry

**CRI > 90:** Available on inquiry

**Weight:** 2100 g