

POLARIS ZK ZK.P4.600.XY


Type: suspension lamp

Lampshade: white, hand-blown, three-layered glass, satin opal matt

Metal parts: painted steel plate RAL 9003 (.31), RAL 9005 (.61), RAL chrom (.77), chrome (.80), stainless steel (.83) or brass (.84)

Pendant: white or black self-carrying conductor reinforced with a steel wire

The luminaire driver is placed right inside the luminaire (LED version).



| W | K | Module luminous flux lm | Luminaire luminous flux lm | A | C | DALI 2 | Motion sensor | Bluetooth | Track system | Weight | |
|------|------|-------------------------|----------------------------|-----|------|--------|---------------|-----------|--------------|--------|-------|
| 55,7 | 4000 | 9168 | 8250 | 600 | 2000 | M | - | P* | Q* | - | 13700 |

Lucis ZK.P4.600.X POLARIS ZK LED / LDC (Polar)

Voltage: 230V

IK code: IK01

Ballast: Driver

CRI: >90

LED life: L80/F10 50000 hours

Watt: 55,7 W

Color temperature: 4000 K

Module luminous flux: 9168 lm

Luminaire luminous flux: 8250 lm

A: 600 mm

C: 2000 mm

Dali 2: Available

Motion sensor: Not available

Emergency module: Available on inquiry

Bluetooth control: Available on inquiry

Track system: Not available

Sádrokarton: Not available

Weight: 13700 g

Luminaire: Lucis ZK.P4.600.X POLARIS ZK LED
Lamps: 1 x LED G6

