

POLARIS ZT ZT.P4.500.XY

**Type:** suspension lamp

**Lampshade:** white, hand-blown, three-layered glass, satin opal matt

**Metal parts:** painted steel plate RAL 9003 (.31), RAL 9005 (.61), RAL chrom (.77), chrome (.80), stainless steel (.83) or brass (.84)

**Pendant:** rod

The luminaire driver is placed right inside the luminaire (LED version).



W	K	Module luminous flux lm	Luminaire luminous flux lm	A	C	DALI 2	Motion sensor	Bluetooth	Track system	Weight		
48,5	4000	7800	7020	500	1000	M	-	P*	Q*	R*	-	8100

**Voltage:** 230V

**IK code:** IK01

**Ballast:** Driver

**CRI:** >90

**LED life:** L80/F10 50000 hours

**Watt:** 48,5 W

**Color temperature:** 4000 K

**Module luminous flux:** 7800 lm

**Luminaire luminous flux:** 7020 lm

**A:** 500 mm

**C:** 1000 mm

**Dali 2:** Available

**Motion sensor:** Not available

**Emergency module:** Available on inquiry

**Bluetooth control:** Available on inquiry

**Track system:** Available on inquiry

**Sádrokarton:** Not available

**Weight:** 8100 g

Lucis ZT.P4.500.X POLARIS ZT LED / LDC (Polar)

Luminaire: Lucis ZT.P4.500.X POLARIS ZT LED  
Lamps: 1 x LED G6

