

POLARIS ZT ZT.P4.600.XY


Type: suspension lamp

Lampshade: white, hand-blown, three-layered glass, satin opal matt

Metal parts: painted steel plate RAL 9003 (.31), RAL 9005 (.61), RAL chrom (.77), chrome (.80), stainless steel (.83) or brass (.84)

Pendant: rod

The luminaire driver is placed right inside the luminaire (LED version).



W	K	Module luminous flux lm	Luminaire luminous flux lm	A	C	DALI 2	Motion sensor	Emergency module	Bluetooth	Track system	Weight	
55,7	4000	9168	8250	600	1000	M	-	P*	Q*	R*	-	13900

Voltage: 230V

IK code: IK01

Ballast: Driver

CRI: >90

LED life: L80/F10 50000 hours

Watt: 55,7 W

Color temperature: 4000 K

Module luminous flux: 9168 lm

Luminaire luminous flux: 8250 lm

A: 600 mm

C: 1000 mm

Dali 2: Available

Motion sensor: Not available

Emergency module: Available on inquiry

Bluetooth control: Available on inquiry

Track system: Available on inquiry

Sádrokarton: Not available

Weight: 13900 g

Lucis ZT.P4.600.X POLARIS ZT LED / LDC (Polar)

Luminaire: Lucis ZT.P4.600.X POLARIS ZT LED
Lamps: 1 x LED G6

