

DAPHNE S24.L4.D350.Y

Type: ceiling and wall lamp

Lampshade: white, hand-blown, three-layered glass, satin opal matt

Light body: white painted steel plate



| W | K | Module luminous flux lm | Luminaire luminous flux lm | A | B | C | D | DALI 2 | Motion sensor | Emergency module | Bluetooth | Track system | Weight |
|------|------|-------------------------|----------------------------|-----|-----|----|-----|--------|---------------|------------------|-----------|--------------|--------|
| 10,7 | 4000 | 1738 | 1324 | 350 | 150 | 20 | 240 | M | O* | - | Q* | - | 2600 |

Lucis S24.L4.D350 DAPHNE LED / LDC (Polar)

Voltage: 230V

IK code: IK01

Ballast: Driver

CRI: >90

LED life: L80/F10 50000 hours

Watt: 10,7 W

Color temperature: 4000 K

Module luminous flux: 1738 lm

Luminaire luminous flux: 1324 lm

A: 350 mm

B: 150 mm

C: 20 mm

D: 240 mm

Dali 2: Available

Motion sensor: Available on inquiry

Emergency module: Not available

Bluetooth control: Available on inquiry

Track system: Not available

Sádrokarton: Not available

Weight: 2600 g

Luminaire: Lucis S24.L4.D350 DAPHNE LED
Lamps: 1 x LED G6

