



## DAPHNE S34.L5.D450.Y

**Type:** ceiling and wall lamp

**Lampshade:** white, hand-blown, three-layered glass, satin opal matt

**Light body:** white painted steel plate



| W    | K    | Module luminous flux lm | Luminaire luminous flux lm | A   | B   | C  | D   | DALI 2 | Motion sensor | Emergency module | Bluetooth | Track system | Weight |
|------|------|-------------------------|----------------------------|-----|-----|----|-----|--------|---------------|------------------|-----------|--------------|--------|
| 21,3 | 3000 | 3216                    | 2377                       | 450 | 180 | 20 | 340 | M      | O*            | P*               | Q*        | -            | 4500   |

Lucis S34.L5.D450 DAPHNE LED / LDC (Polar)

**Voltage:** 230V

**IK code:** IK01

**Ballast:** Driver

**CRI:** >90

**LED life:** L80/F10 50000 hours

**Watt:** 21,3 W

**Color temperature:** 3000 K

**Module luminous flux:** 3216 lm

**Luminaire luminous flux:** 2377 lm

**A:** 450 mm

**B:** 180 mm

**C:** 20 mm

**D:** 340 mm

**Dali 2:** Available

**Motion sensor:** Available on inquiry

**Emergency module:** Available on inquiry

**Bluetooth control:** Available on inquiry

**Track system:** Not available

**Sádrokarton:** Not available

**Weight:** 4500 g

Luminaire: Lucis S34.L5.D450 DAPHNE LED  
Lamps: 1 x LED G6

