


DAPHNE IP44 PS13.L6.D550.Y

**Type:** ceiling and wall lamp

**Lampshade:** white, hand-blown, three-layered glass, satin opal matt

**Light body:** white painted steel plate



W	K	Module luminous flux lm	Luminaire luminous flux lm	A	B	C	D	DALI 2	Motion sensor	Emergency module	Bluetooth	Track system	Weight
26,7	4000	4345	3142	550	200	13	450	M	O*	P*	Q*	-	7800

Lucis PS13.L6.D550 DAPHNE LED / LDC (Polar)

**Voltage:** 230V

**IK code:** IK01

**Ballast:** Driver

**CRI:** >90

**LED life:** L80/F10 50000 hours

**Watt:** 26,7 W

**Color temperature:** 4000 K

**Module luminous flux:** 4345 lm

**Luminaire luminous flux:** 3142 lm

**A:** 550 mm

**B:** 200 mm

**C:** 13 mm

**D:** 450 mm

**Dali 2:** Available

**Motion sensor:** Available on inquiry

**Emergency module:** Available on inquiry

**Bluetooth control:** Available on inquiry

**Track system:** Not available

**Sádrokarton:** Not available

**Weight:** 7800 g

Luminaire: Lucis PS13.L6.D550 DAPHNE LED  
Lamps: 1 x LED G6

