



DAPHNE ZT ZT.L5.D550.XY

Type: suspension lamp

Lampshade: white, hand-blown, three-layered glass, satin opal matt

Pendant: white painted steel RAL 9003 (.31), chrome (.80), brass (.84), RAL chrom (.77) or RAL Argento dorato (.70) rod suspension



W	K	Module luminous flux lm	Luminaire luminous flux lm	A	B	C	DALI 2	IK10	IK15	Bluetooth	Emergency	Weight
26,7	3000	4020	2893	550	245	1000	M	-	P*	Q*	R*	8600

Lucis ZT.L5.D550.X DAPHNE LED / LDC (Polar)

Voltage: 230V

IK code: IK01

Ballast: Driver

CRI: >90

LED life: L80/F10 50000 hours

Watt: 26,7 W

Color temperature: 3000 K

Module luminous flux: 4020 lm

Luminaire luminous flux: 2893 lm

A: 550 mm

B: 245 mm

C: 1000 mm

Dali 2: Available

Motion sensor: Not available

Emergency module: Available on inquiry

Bluetooth control: Available on inquiry

Track system: Available on inquiry

Sádrokarton: Not available

Weight: 8600 g

Luminaire: Lucis ZT.L5.D550.X DAPHNE LED
Lamps: 1 x LED G6

