


DAPHNE ZT ZT.L6.D550.XY

Type: suspension lamp

Lampshade: white, hand-blown, three-layered glass, satin opal matt

Pendant: white painted steel RAL 9003 (.31), chrome (.80), brass (.84), RAL chrom (.77) or RAL Argento dorato (.70) rod suspension



W	K	Module luminous flux lm	Luminaire luminous flux lm	A	B	C	DALI 2	IK	IP	Bluetooth	Emergency	Weight
26,7	4000	4345	3142	550	245	1000	M	-	P*	Q*	R*	8600

Lucis ZT.L6.D550.X DAPHNE LED / LDC (Polar)

Voltage: 230V

IK code: IK01

Ballast: Driver

CRI: >90

LED life: L80/F10 50000 hours

Watt: 26,7 W

Color temperature: 4000 K

Module luminous flux: 4345 lm

Luminaire luminous flux: 3142 lm

A: 550 mm

B: 245 mm

C: 1000 mm

Dali 2: Available

Motion sensor: Not available

Emergency module: Available on inquiry

Bluetooth control: Available on inquiry

Track system: Available on inquiry

Sádrokarton: Not available

Weight: 8600 g

Luminaire: Lucis ZT.L6.D550.X DAPHNE LED
Lamps: 1 x LED G6

