



POLARIS S BS24.L2.350.XY

Type: ceiling and wall lamp

Lampshade: white, hand-blown, three-layered glass, satin opal matt

Light body: painted aluminium - RAL white 9016 (.41), RAL black 9005 (.45), RAL Copper (.72), RAL Bronze (.73) or RAL Brass (.74)

The ceiling version has IP44 rating of ingress protection, the wall version has IP40.



W	K	Module luminous flux lm	Luminaire luminous flux lm	A	B	C	DALI 2	Motion sensor	Emergency module	Bluetooth	Track system	Weight
15,7	4000	2303	2072	350	240	345	M	O*	-	Q*	-	3600

Lucis BS24.L2.350.X POLARIS S LED / LDC (Polar)

Voltage: 230V

IK code: IK01

Ballast: Driver

CRI: >90

LED life: L80/F10 50000 hours

Watt: 15,7 W

Color temperature: 4000 K

Module luminous flux: 2303 lm

Luminaire luminous flux: 2072 lm

A: 350 mm

B: 240 mm

C: 345 mm

Dali 2: Available

Motion sensor: Available on inquiry

Emergency module: Not available

Bluetooth control: Available on inquiry

Track system: Not available

Sádrokarton: Not available

Weight: 3600 g

Luminaire: Lucis BS24.L2.350.X POLARIS S LED
Lamps: 1 x LED G6

