



**DAPHNE ZL ZL3.L6.D451.31Y**

**Type:** suspension lamp

**Lampshade:** white, hand-blown, three-layered glass, satin opal matt

**Metal parts:** painted steel plate RAL 9003 (.31), RAL chrom (.77)

**Pendant:** wire suspension with white cable



W	K	Module luminous flux lm	Luminaire luminous flux lm	A	B	C	D	DALI 2	IK10	IK15	Bluetooth	Emergency	Weight
16	4000	2607	2052	450	200	2000	max. 1000	M	-	P*	Q*	-	6200

Lucis ZL3.L6.D451.X DAPHNE LED / LDC (Polar)

**Voltage:** 230V

**IK code:** IK01

**Ballast:** Driver

**CRI:** >90

**LED life:** L80/F10 50000 hours

**Watt:** 16 W

**Color temperature:** 4000 K

**Module luminous flux:** 2607 lm

**Luminaire luminous flux:** 2052 lm

**A:** 450 mm

**B:** 200 mm

**C:** 2000 mm

**D:** max. 1000 mm

**Dali 2:** Available

**Motion sensor:** Not available

**Emergency module:** Available on inquiry

**Bluetooth control:** Available on inquiry

**Track system:** Not available

**Sádrokarton:** Not available

**Weight:** 6200 g

Luminaire: Lucis ZL3.L6.D451.X DAPHNE LED  
Lamps: 1 x LED G6

