



PALA SR.L1.P1.45M.Y

Type: ceiling and wall lamp

Lampshade: white, hand-blown, three-layered glass, satin opal matt

Metal parts: painted steel plate RAL 9005 (.45) or with a reflective highly polished brass-coated disc (.45M)



| W | K | Module luminous flux lm | Luminaire luminous flux lm | A | B | C | DALI 2 | Motion sensor | Emergency module | Bluetooth control | Track system | Weight |
|-----|------|-------------------------|----------------------------|-----|-----|-----|--------|---------------|------------------|-------------------|--------------|--------|
| 8,3 | 3000 | 1060 | 899 | 365 | 340 | 200 | M | - | - | - | - | 3000 |

Lucis SR.L1.P1.45M PALA LED / LDC (Polar)

IK code: IK01

Ballast: Driver

CRI: >90

LED life: L80/F10 50000 hours

Watt: 8,3 W

Color temperature: 3000 K

Module luminous flux: 1060 lm

Luminaire luminous flux: 899 lm

A: 365 mm

B: 340 mm

C: 200 mm

Dali 2: Available

Motion sensor: Not available

Emergency module: Not available

Bluetooth control: Not available

Track system: Not available

Sádrokarton: Not available

Weight: 3000 g

Luminaire: Lucis SR.L1.P1.45M PALA LED
Lamps: 1 x LED G6

