


PALA SR.L2.P1.45.Y

**Type:** ceiling and wall lamp

**Lampshade:** white, hand-blown, three-layered glass, satin opal matt

**Metal parts:** painted steel plate RAL 9005 (.45) or with a reflective highly polished brass-coated disc (.45M)



| W   | K    | Module<br>luminous<br>flux lm | Luminaire<br>luminous<br>flux lm | A   | B   | C   | DALI<br>2 | Person<br>with<br>cane | Person<br>in<br>wheelchair | Bluetooth | Emergency | Weight |
|-----|------|-------------------------------|----------------------------------|-----|-----|-----|-----------|------------------------|----------------------------|-----------|-----------|--------|
| 8,3 | 4000 | 1146                          | 971                              | 365 | 340 | 200 | M         | -                      | -                          | -         | -         | 3000   |

Lucis SR.L2.P1.45 PALA LED / LDC (Polar)

**IK code:** IK01

**Ballast:** Driver

**CRI:** >90

**LED life:** L80/F10 50000 hours

**Watt:** 8,3 W

**Color temperature:** 4000 K

**Module luminous flux:** 1146 lm

**Luminaire luminous flux:** 971 lm

**A:** 365 mm

**B:** 340 mm

**C:** 200 mm

**Dali 2:** Available

**Motion sensor:** Not available

**Emergency module:** Not available

**Bluetooth control:** Not available

**Track system:** Not available

**Sádrokarton:** Not available

**Weight:** 3000 g

Luminaire: Lucis SR.L2.P1.45 PALA LED  
Lamps: 1 x LED G6

