


TENDO PMMA S44.K3.TEZ4.Y

**Type:** ceiling and wall lamp

**Lampshade:** acrylic glass PMMA

**Light body:** white painted steel plate



W	K	Module luminous flux lm	Luminaire luminous flux lm	A	B	C	D	DALI 2	Motion sensor	Emergency module	Bluetooth	Track system	Weight
29	3000	3945	2916	460	440	80	20	M	O*	P*	Q*	-	2600

**Voltage:** 230V

**Ballast:** Driver

**IK code:** IK10

**CRI:** >90

**LED life:** L80/F10 50000 hours

**Watt:** 29 W

**Color temperature:** 3000 K

**Module luminous flux:** 3945 lm

**Luminaire luminous flux:** 2916 lm

**A:** 460 mm

**B:** 440 mm

**C:** 80 mm

**D:** 20 mm

**Dali 2:** Available

**Motion sensor:** Available on inquiry

**Emergency module:** Available on inquiry

**Bluetooth control:** Available on inquiry

**Track system:** Not available

**Sádrokarton:** Not available

**Weight:** 2600 g

Lucis S44.K3.TEZ4 TENDO LED / LDC (Polar)

Luminaire: Lucis S44.K3.TEZ4 TENDO LED  
Lamps: 1 x LED G5

