

POLARIS ZKS.P ZKS.P6.400.XM


**Type:** suspension lamp

**Lampshade:** white, hand-blown, three-layered glass, satin opal matt

**Metal parts:** painted steel plate RAL 9003 (.31), RAL 9005 (.61), RAL chrom (.77), chrome (.80) or brass (.84)

**Pendant:** white or black self-carrying conductor reinforced with a steel wire

POLARIS ZKS.P luminaires are **\*\*supplied as DALI dimmable\*\*** as standard equipment. Driver of the luminaire is placed inside the ceiling rose.



| W    | K    | Module luminous flux lm | Luminaire luminous flux lm | A   | C    | DALI 2 | Motion sensor | Emergency module | Bluetooth | Track system | Weight |
|------|------|-------------------------|----------------------------|-----|------|--------|---------------|------------------|-----------|--------------|--------|
| 48,5 | 4000 | 7800                    | 7020                       | 400 | 2000 | M      | -             | P*               | Q*        | -            | 6000   |

**Voltage:** 230V

**IK code:** IK01

**Ballast:** Driver

**CRI:** >90

**LED life:** L80/F10 50000 hours

**Watt:** 48,5 W

**Color temperature:** 4000 K

**Module luminous flux:** 7800 lm

**Luminaire luminous flux:** 7020 lm

**A:** 400 mm

**C:** 2000 mm

**Dali 2:** Available

**Motion sensor:** Not available

**Emergency module:** Available on inquiry

**Bluetooth control:** Available on inquiry

**Track system:** Not available

**Sádrokarton:** Not available

**Weight:** 6000 g

Lucis ZKS.P6.400.X POLARIS ZKS.P LED / LDC (Polar)

Luminaire: Lucis ZKS.P6.400.X POLARIS ZKS.P LED  
Lamps: 1 x LED G6

