

MAIA B ZK.L1B.M620.Y



Type: suspension lamp

Lampshade: white, hand-blown, three-layered glass, satin opal matt

Metal parts: white painted steel plate

Pendant: self-supporting white cable reinforced with a steel wire

The luminaire driver is placed right inside the luminaire.



W	K	Module luminous flux lm	Luminaire luminous flux lm	A	B	C	DALI 2	Motion sensor	Emergency module	Bluetooth	Track system	Weight
43,9	3000	6025	4523	150	620	2000	M	-	-	Q*	R*	6100

Voltage: 230V

IK code: IK01

Ballast: Driver

CRI: >90

LED life: L80/F10 50000 hours

Watt: 43,9 W

Color temperature: 3000 K

Module luminous flux: 6025 lm

Luminaire luminous flux: 4523 lm

A: 150 mm

B: 620 mm

C: 2000 mm

Dali 2: Available

Motion sensor: Not available

Emergency module: Not available

Bluetooth control: Available on inquiry

Track system: Available on inquiry

Sádrokarton: Not available

Weight: 6100 g

Lucis ZK.L1B.M620 MAIA LED / LDC (Polar)

Luminaire: Lucis ZK.L1B.M620 MAIA LED
Lamps: 1 x LED G5

