

MAIA B ZK.L3B.M500.Y



Type: suspension lamp

Lampshade: white, hand-blown, three-layered glass, satin opal matt

Metal parts: white painted steel plate

Pendant: self-supporting white cable reinforced with a steel wire

The luminaire driver is placed right inside the luminaire.



W	K	Module luminous flux lm	Luminaire luminous flux lm	A	B	C	DALI 2	Motion sensor	Emergency	Bluetooth	Track system	Weight	
27,4	3000	3978	2986	150	500	2000	M	-	P*	Q*	R*	D*	3800

Voltage: 230V

IK code: IK01

Ballast: Driver

CRI: >90

LED life: L80/F10 50000 hours

Watt: 27,4 W

Color temperature: 3000 K

Module luminous flux: 3978 lm

Luminaire luminous flux: 2986 lm

A: 150 mm

B: 500 mm

C: 2000 mm

Dali 2: Available

Motion sensor: Not available

Emergency module: Available on inquiry

Bluetooth control: Available on inquiry

Track system: Available on inquiry

Sádrokarton: Available on inquiry

Weight: 3800 g

Lucis ZK.L3B.M500 MAIA LED / LDC (Polar)

Luminaire: Lucis ZK.L3B.M500 MAIA LED
Lamps: 1 x LED G5

