

MAIA B ZK.L2B.M800.Y

Type: suspension lamp

Lampshade: white, hand-blown, three-layered glass, satin opal matt

Metal parts: white painted steel plate

Pendant: self-supporting white cable reinforced with a steel wire

The luminaire driver is placed right inside the luminaire.



W	K	Module luminous flux lm	Luminaire luminous flux lm	A	B	C	DALI 2	Motion sensor	Emergency module	Bluetooth	Track system	Weight
109,9	4000	15157	11362	220	800	2000	M	-	-	Q*	R*	8300

Voltage: 230V

IK code: IK01

Ballast: Driver

CRI: >90

LED life: L80/F10 50000 hours

Watt: 109,9 W

Color temperature: 4000 K

Module luminous flux: 15157 lm

Luminaire luminous flux: 11362 lm

A: 220 mm

B: 800 mm

C: 2000 mm

Dali 2: Available

Motion sensor: Not available

Emergency module: Not available

Bluetooth control: Available on inquiry

Track system: Available on inquiry

Sádrokarton: Not available

Weight: 8300 g

Lucis ZK.L2B.M800 MAIA LED / LDC (Polar)

Luminaire: Lucis ZK.L2B.M800 MAIA LED
Lamps: 1 x LED G5

