

MAIA B ZK.L2B.M620.Y


Type: suspension lamp

Lampshade: white, hand-blown, three-layered glass, satin opal matt

Metal parts: white painted steel plate

Pendant: self-supporting white cable reinforced with a steel wire

The luminaire driver is placed right inside the luminaire.



| W | K | Module luminous flux lm | Luminaire luminous flux lm | A | B | C | DALI 2 | Motion sensor | Emergency module | Bluetooth | Track system | Weight |
|------|------|-------------------------|----------------------------|-----|-----|------|--------|---------------|------------------|-----------|--------------|--------|
| 43,9 | 4000 | 6312 | 4738 | 150 | 620 | 2000 | M | - | - | Q* | R* | 6100 |

Voltage: 230V

IK code: IK01

Ballast: Driver

CRI: >90

LED life: L80/F10 50000 hours

Watt: 43,9 W

Color temperature: 4000 K

Module luminous flux: 6312 lm

Luminaire luminous flux: 4738 lm

A: 150 mm

B: 620 mm

C: 2000 mm

Dali 2: Available

Motion sensor: Not available

Emergency module: Not available

Bluetooth control: Available on inquiry

Track system: Available on inquiry

Sádrokarton: Not available

Weight: 6100 g

Lucis ZK.L2B.M620 MAIA LED / LDC (Polar)

Luminaire: Lucis ZK.L2B.M620 MAIA LED
Lamps: 1 x LED G5

