

MAIA B PMMA ZK.L2B.M320.Y PA


**Type:** suspension lamp

**Lampshade:** acrylic glass PMMA

**Metal parts:** white painted steel plate

**Pendant:** self-supporting white cable reinforced with a steel wire

The luminaire driver is placed right inside the luminaire.



W	K	Module luminous flux lm	Luminaire luminous flux lm	A	B	C	DALI 2	Motion sensor	Emergency module	Bluetooth	Track system	Weight	
14,5	4000	2103	1680	150	320	2000	M	-	P*	-	R*	D*	1800

**Voltage:** 230V

**IK code:** IK06

**Ballast:** Driver

**CRI:** >90

**LED life:** L80/F10 50000 hours

**Watt:** 14,5 W

**Color temperature:** 4000 K

**Module luminous flux:** 2103 lm

**Luminaire luminous flux:** 1680 lm

**A:** 150 mm

**B:** 320 mm

**C:** 2000 mm

**Dali 2:** Available

**Motion sensor:** Not available

**Emergency module:** Available on inquiry

**Bluetooth control:** Not available

**Track system:** Available on inquiry

**Sádrokarton:** Available on inquiry

**Weight:** 1800 g

Lucis ZK.L2B.M320 PA MAIA LED / LDC (Polar)

Luminaire: Lucis ZK.L2B.M320 PA MAIA LED  
Lamps: 1 x LED G5

