

MAIA B PMMA ZK.L1B.M620.Y PA


Type: suspension lamp

Lampshade: acrylic glass PMMA

Metal parts: white painted steel plate

Pendant: self-supporting white cable reinforced with a steel wire

The luminaire driver is placed right inside the luminaire.



W	K	Module luminous flux lm	Luminaire luminous flux lm	A	B	C	DALI 2	Motion sensor	Emergency module	Bluetooth	Track system	Weight	
43,9	3000	6025	4804	150	620	2000	M	-	P*	-	R*	D*	3400

Voltage: 230V

IK code: IK06

Ballast: Driver

CRI: >90

LED life: L80/F10 50000 hours

Watt: 43,9 W

Color temperature: 3000 K

Module luminous flux: 6025 lm

Luminaire luminous flux: 4804 lm

A: 150 mm

B: 620 mm

C: 2000 mm

Dali 2: Available

Motion sensor: Not available

Emergency module: Available on inquiry

Bluetooth control: Not available

Track system: Available on inquiry

Sádrokarton: Available on inquiry

Weight: 3400 g

Lucis ZK.L1B.M620 PA MAIA LED / LDC (Polar)

Luminaire: Lucis ZK.L1B.M620 PA MAIA LED
Lamps: 1 x LED G5

