




SEMILUNA ZT6.L2.S200.XY

**Type:** luminaire suspendu

**Abat-jour:** verre blanc, soufflé de manière artisanale, à trois couches, satin opale mat

**Les pièces métalliques:** acier laqué RAL 9003 (.60), RAL 9005 (.61), RAL Bronze (.73) ou RAL Chrom (.77)

**Suspension:** tube



W	K	Module luminous flux lm	Luminaire luminous flux lm	A	B	C	DALI 2	IK01	Q*	Weight
43,3	4000	7074	4244	1050	200	850	M	-	-	17400

Lucis ZT6.L2.S200.X\_pc(6) SEMILUNA LED / LDC (Polar)

**Tension:** 230V

**IK code:** IK01

**Ballaste:** Driver

**CRI:** >90

**La vie de LED:** L80/F10 50000 heures

**Watt:** 43,3 W

**Température Couleur:** 4000 K

**Module luminous flux:** 7074 lm

**Luminaire luminous flux:** 4244 lm

**A:** 1050 mm

**B:** 200 mm

**C:** 850 mm

**Dali 2:** Disponible

**Capteur de mouvement:** Non disponible

**Module d'urgence:** Non disponible

**Contrôle Bluetooth:** Disponible sur demande

**Track system:** Non disponible

**Sádrokarton:** Non disponible

**Poids:** 17400 g

Luminaire: Lucis ZT6.L2.S200.X\_pc(6) SEMILUNA LED  
Lamps: 1 x LED G6

