


SEMILUNA ZT.L1.S150.XY

**Type:** suspension lamp

**Lampshade:** white, hand-blown, three-layered glass, satin opal matt

**Metal parts:** painted steel plate RAL 9003 (.60), RAL 9005 (.61), RAL Bronze (.73) or RAL Chrom (.77)

**Pendant:** rod



W	K	Module luminous flux lm	Luminaire luminous flux lm	A	C	DALI 2	Icon 1	Icon 2	Icon 3	Icon 4	Icon 5	Icon 6
6,2	3000	804	482	150	1000	M	-	P*	Q*	-	-	1700

**Voltage:** 230V

**IK code:** IK01

**Ballast:** Driver

**CRI:** >90

**LED life:** L80/F10 50000 hours

**Watt:** 6,2 W

**Color temperature:** 3000 K

**Module luminous flux:** 804 lm

**Luminaire luminous flux:** 482 lm

**A:** 150 mm

**C:** 1000 mm

**Dali 2:** Available

**Motion sensor:** Not available

**Emergency module:** Available on inquiry

**Bluetooth control:** Available on inquiry

**Track system:** Not available

**Sádrokarton:** Not available

**Weight:** 1700 g

Lucis ZT.L1.S150.X SEMILUNA LED / LDC (Polar)

Luminaire: Lucis ZT.L1.S150.X SEMILUNA LED  
Lamps: 1 x LED G6

