

GEO ZK2.L2.GA.61Y



**Type:** suspension lamp

**Lampshade:** white, hand-blown, three-layered glass, satin opal matt

**Metal parts:** painted steel plate RAL 9005 (.61)

**Pendant:** black cable

Mounting options: ceiling/ceiling (A), ceiling/track (B), track/track (C) or plasterboard (D)



W	K	Module luminous flux lm	Luminaire luminous flux lm	A	B	C	D	DALI 2	IK01	IK02	Bluetooth	Manual	Person
6,2	4000	869	736	400	955	1150	150	M	-	-	-	-	1300

**Voltage:** 230V

**IK code:** IK01

**Ballast:** Driver

**CRI:** >90

**LED life:** L80/F10 50000 hours

**Watt:** 6,2 W

**Color temperature:** 4000 K

**Module luminous flux:** 869 lm

**Luminaire luminous flux:** 736 lm

**A:** 400 mm

**B:** 955 mm

**C:** 1150 mm

**D:** 150 mm

**Dali 2:** Available

**Motion sensor:** Not available

**Bluetooth control:** Not available

**Track system:** Not available

**Sádrokarton:** Not available

**Weight:** 1300 g

**Lucis ZK2.L2.GA.61\_pc(1) GEO LED / LDC (Polar)**

Luminaire: Lucis ZK2.L2.GA.61\_pc(1) GEO LED  
Lamps: 1 x LED G6

